

## **DECLARATION OF PERFORMANCE**

(according to Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended

Document no.:

TEC-DOP-UKC4003H

Revision 0

For the construction products: Hot Rolled Strip & Sheet of Corrosion Resisting Steel					
1.	Identification code of the product-type		1.4003 – EN 10088-4:2009		
2.	Туре		1.4003 See marking / label / inspection certificate		
3.	Intended use		Building Construction or Civil Engineering		
			Columbus Stainless (Pty) Ltd		
4.	Manufacturer		Hendrina Road, Middelburg, South Africa,		
				1050	
II _	Authorized Penrocentative in the LIV		Acerinox U.K. Ltd., Heath Road, Darlaston West		
5.	Authorised Representative in the UK		Midlands WS10 8XL		
6.	Assessment system and verification for		EN 10088-4, Annex ZA, System 2+		
<u> </u> -	constancy of performance as per Annex V				
ll .	The Notified Body:		TUV Rheinland UK Ltd. 2+ 2571-UK-CPR-A304		
	has conducted the first inspection and				
_	continuous surveillance according to the				
7.	system:				
	and issued the certificate:	for the feetens	25/1-UK	-CPR-A304	
	as a confirmation of conformity	for the factory			
-	Production control  Construction product with European Technical Assessment: No				
8. 9.					
<u> 9.</u>					
				T	
	<b>Essential Characteristics</b>	Performa	nce	Harmonised Technical Specification	
	Tolerances on Dimensions	Tables 1 to 10		-	
	Tolerances on Dimensions and Shape			Harmonised Technical Specification EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties -	Tables 1 to 10		-	
	Tolerances on Dimensions and Shape Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,		-	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength	Tables 1 to 10 Paragraphs 9, 450-600MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥320MPa		-	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥320MPa		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20%		EN 10051:2010	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥320MPa ≥20% N/A		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by	Tables 1 to 10 Paragraphs 9, 450-600MPa ≥320MPa ≥20% N/A		EN 10051:2010  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength  Elongation  • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20% N/A Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20% N/A Table 1  Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20% N/A Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20% N/A  Table 1  Table 1  Table 7		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength  • 0.2% Proof strength Elongation • Impact strength  Weldability [Covered by chemical composition]  Durability [Covered by chemical composition]  Fracture Toughness / Brittle Strength [Covered by impact strength]  Cold Formability [Covered by	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20% N/A Table 1  Table 1		EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	
	Tolerances on Dimensions and Shape  Mechanical Properties - Transverse:  • Tensile strength • 0.2% Proof strength Elongation • Impact strength Weldability [Covered by chemical composition] Durability [Covered by chemical composition] Fracture Toughness / Brittle Strength [Covered by impact strength]	Tables 1 to 10 Paragraphs 9,  450-600MPa ≥320MPa ≥20% N/A  Table 1  Table 1  Table 7	10 & 11	EN 10051:2010  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009  EN 10088-4:2009	

10. The performance of the product is in accordance with the specification given above. This Declaration of Performance is issued under the sole responsibility of Columbus Stainless (Pty) Ltd.

Signed for and on behalf of the manufacturer by:

DJ Kruger: Business Unit Manager Technical

Signed at Middelburg, South Africa on the 6<sup>th</sup> day of March 2024